

SHURE®

LEGENDARY
PERFORMANCE™



SLX® WIRELESS SYSTEMS

**SMART, HARD-WORKING
WIRELESS.**

SLX® Wireless Microphone Systems

EVERYWHERE WIRELESS.

Whether it's for a sound installation or a working band on the road, audio professionals need powerful wireless tools that can be set up quickly and used confidently. Shure's rugged SLX Wireless Systems exceed these demands with innovative automatic setup features, exceptional wireless clarity and legendary Shure microphones. Supporting up to 20 compatible systems across multiple UHF frequency bands, SLX smoothly integrates into houses of worship, lecture halls, conference rooms and mobile gear cases.

Shure's patented Audio Reference Companding

Delivers crystal-clear audio transmission, far superior to conventional wireless technology

Auto Frequency Selection

Locates a clear channel instantly

Auto Transmitter Setup

Infrared link automatically syncs the transmitter and receiver



Wireless Receiver

- Detachable ¼ wave antennas
- Backlit LCD
- Rack-mount hardware included
- ¼" and XLR audio outputs
- Frequency and power lockout
- Volume control on rear of unit
- Rugged metal construction

Handheld or Bodypack Transmitter

- Choice of Shure handheld microphones
- Bodypack works with headworn, lavalier and instrument microphones and cables
- Timed backlit LCD
- Frequency and power lockout
- 2 AA batteries (included) provide 8 hours of continuous use
- 100m (300 ft.) operating range

Available System Options

Handheld



SM58®
SM86
BETA 58A®

BETA 87A
BETA 87C

Systems include:

SLX4 Diversity Receiver and a choice of Handheld Microphone Transmitter.

SLX24/SM58
SLX24/SM86
SLX24/BETA58

SLX24/BETA87A
SLX24/BETA87C

Lavalier



WL93
WL184
WL185

Systems include:

SLX4 Diversity Receiver, SLX1 Bodypack Transmitter and a choice of Microphone or Guitar/Bass Cable.

SLX14/93 SLX14/SM35 SLX14 SLX14/BETA98H
SLX14/84
SLX14/85

Headworn



SM35*
*Available in select regions.

Guitar



WA302

Instrument



WB98H/C

Combo



SM58®
WL185



Wireless Microflex® Boundary/Gooseneck



MX690



MX405
with MX890



MX410
with MX890

System includes:

SLX4 Diversity Receiver, SLX1 Bodypack Transmitter and SLX2 handheld Transmitter.

SLX124/85/SM58

Microflex Microphones are sold as components only.

Optional Accessories

- UA221** Passive Antenna Splitter
- UA505** Remote Mount Kit for ½ wave antennas
- UA820** ½ Wave Antennas
- UA825** 25' cable for ½ wave antennas
- UA844SWB** Antenna/Power Distribution System
- UA850** 50' cable for ½ wave antennas
- UA830** Active Remote Antenna Kit (UA844 required)
- UA870** Active Directional Antenna (UA844 required)
- WA610** Universal Hard Carrying Case transmitter

Optional Logic Functionality

- A logic circuit and associated block connector is provided on the SLX4L receiver, designed to function optimally with software echo cancellers and provide remote monitoring of transmitter battery life. Supported models include MX690, MX890, and SLX4L receiver.
- SLX4L** Wireless Receiver with Logic
 - MX690** Wireless Microflex® Boundary Microphone
 - MX890** Wireless Microflex® Desktop Base

System Specifications

NOTE: All specifications are subject to change.

Frequency Range and Transmitter Output Level

Band	Range	SLX1/SLX2	MX690/ MX890
H5	518–542 MHz	30 mW	10 mW
J3	572–596 MHz	28 mW	28 mW
L4	638–662 MHz	30 mW	10 mW
P4	702–726 MHz	30 mW	10 mW
R5	800–820 MHz	20 mW	10 mW
S6	838–865 MHz	10 mW	10 mW
JB	806–810 MHz	10 mW	10 mW
Q4	740–752 MHz	10 mW	10 mW
R13	794–806 MHz	20 mW	10 mW
G4	470–494 MHz	30 mW	10 mW
G5	494–518 MHz	30 mW	10 mW

Operating Range:

30–100 m (100–300 ft.) under typical conditions, depending on transmitter type

Note: actual range depends on RF signal absorption, reflection, and interference.

Audio Frequency Response:

Minimum: 45 Hz, Maximum: 15 kHz (± 2 dB)

Total Harmonic Distortion:

0.5%, typical (ref. ± 38 kHz deviation, 1 kHz tone)

Dynamic Range:

>100 dB A-weighted

Operating Temperature Range:

-18°C (0°F) to $+50^{\circ}\text{C}$ ($+122^{\circ}\text{F}$)

Note: battery characteristics may limit this range.

Transmitter Audio Polarity:

Positive pressure on microphone diaphragm (or positive voltage applied to tip of WA302 phone plug) produces positive voltage on pin 2 (with respect to pin 3 of low impedance output) and the tip of the high impedance ¼-inch output.

NOTE: This radio apparatus may be capable of operating on some frequencies not authorized in your region. Please contact your national authority to obtain information on authorized frequencies and output power levels for wireless microphone products in your region.



- No “breathing” noise
- Lower noise floor
- More headroom - won't clip as easily
- Clearer sound at all audio levels
- Sounds more like a wired mic

SHURE[®]
LEGENDARY
PERFORMANCE™

**United States, Canada,
Latin America, Caribbean:**
Shure Incorporated
5800 West Touhy Avenue
Niles, IL 60714-4608 USA


Phone: +1 847-600-2000
Fax: +1 847-600-1212 (USA)
Fax: +1 847-600-6446
Email: info@shure.com
www.shure.com

Component Specifications

Receiver Handheld Transmitter Bodypack Transmitter



SLX4 Receiver Front



SLX4 Receiver Rear



SLX4L Receiver Rear



SLX4/SLX4L

Housing:
Galvanized steel

Audio Output Level:
(ref. ± 38 kHz deviation with 1 kHz tone)
XLR connector (into 600 Ω load):
-13 dBV
¼ inch connector (into 3000 Ω load):
-2 dBV

Sensitivity:
-105 dBm for 12 dB SINAD, typical

Image Rejection
>70 dB, typical

Power:
12–18 Vdc at 150 mA, supplied by external power supply

Weight:
816 g (1 lb. 13 oz.)

Dimensions:
42 mm H x 197 mm W x 134 mm D

SLX2

Housing:
Molded ABS handle and battery cup

Audio Input Level:
-8 dBV maximum at 0dB position

Operating range:
100 m (300 ft.)

Power Requirements:
2 “AA” size alkaline or rechargeable batteries

Battery Life (alkaline):
>8 hours

Weight:
290 grams (10.2 oz.) without batteries

Dimensions:
254 mm x 51 mm dia.
(incl. SM58 cartridge)

SLX1

Housing:
Molded ABS case

Audio Input Level:
+10 dBV max. at 0 dB gain position

Operating range:
100 m (300 ft.)


Power Requirements:
2 “AA” size alkaline or rechargeable batteries

Battery Life (alkaline):
>8 hours

Weight:
81 grams (3 oz.) without batteries

Dimensions:
108 mm H x 64 mm W x 19 mm D

Wireless Boundary Microphone Gooseneck Microphone with Wireless Desktop Base



MX690

Operating Range:
30 m (100 ft.) Note: Actual range depends on RF signal absorption, reflection, and interference

Type:
Condenser (electret bias)


Polar Pattern (at 1 kHz):
Cardioid

Power Requirements:
2 “AA” size alkaline or rechargeable batteries

Battery Life:
 ≥ 8 hours (alkaline)

Dimensions:
43 mm H x 87 mm W x 148 mm D

Weight:
Net: 318 g (11.2 oz)
Packaged: 516 g (18.2 oz)



MX405 & MX410

Type:
Condenser (electret bias)

Polar Pattern:
MX405/C, MX410/C: Cardioid
MX405/S, MX410/S:
Supercardioid

Weight:
Net MX405: 54 g (1.9 oz)
Net MX410: 68 g (2.3 oz)

Dimensions:
MX405: 152mm L x 7.5mm dia.
MX410: 251 mm L x 7.5 mm dia.



MX890

Operating Range:
30 m (100 ft.) Note: Actual range depends on RF signal absorption, reflection, and interference

Power Requirements:
2 “AA” size alkaline or rechargeable batteries

Battery Life:
 ≥ 8 hours (alkaline)

Weight:
Net: 312 g (11 oz)

Dimensions
43 mm H x 87 mm W x 148 mm D

Europe, Middle East, Africa:
Shure Europe GmbH
Jakob-Dieffenbacher-Str. 12,
75031 Eppingen, Germany

Phone: +49-7262-92490
Fax: +49-7262-9249114
Email: info@shure.de
www.shure.eu

Asia, Pacific:
Shure Asia Limited
22/F, 625 King's Road
North Point, Island East
Hong Kong

Phone: +852-2893-4290
Fax: +852-2893-4055
Email: info@shure.com.hk
www.shureasia.com