

# 220V-240V CLASSIC SERIES POWER CONDITIONERS



Furman brings together superior protection and outstanding performance in a sturdy, rack-mountable design. Classic Series Power Conditioners feature Series Multi-Stage Protection (SMP), Linear Filtering Technology (LiFT), Extreme Voltage Shutdown (EVS), and offer a new industrial design and full feature set engineered specifically for the A/V professional.



## PL-8C E FEATURES



## PL-PLUS C E FEATURES



## PL-PRO DMC E FEATURES






# FURMAN


WWW.FURMANSOUND.COM

# THE POWER OF **FURMAN** TECHNOLOGY

## PL-8C E FEATURES:



## ADDITIONAL PL-PLUS C E FEATURES:



\*Models come equipped with a 2.5M cord with IEC female to male Schuko plug. Adapter cords are available separately. Please ask your Furman Representative for further information about your adapter needs.

## CLASSIC SERIES REAR PANEL



PL-8C E/PL-PLUS C E REAR PANEL



PL-PRO DMC E REAR PANEL

## CLASSIC SERIES SPECIFICATIONS

**MAXIMUM OUTPUT CURRENT:**  
10 AMPS (PL-8 C E, PL-PLUS C E) - 16 AMPS (PL-PRO DMC E)

**LINE CORD:**  
3/1.0MM AWG, 2.5M CORD W/IEC FEMALE TO 10A SCHUKO PLUG

**PULL OUT LIGHTS:**  
TWO MULTI-LED, "SMOOTH TRACK" DIMMABLE LAMPS

**BNC SOCKET W/SWITCH:**  
REAR RACK LAMP, 12VAC 500MA MAX (LAMP NOT INCLUDED)

**OPERATING VOLTAGE:**  
180 TO 274 VAC

**OVER VOLTAGE SHUTDOWN:**  
275 VAC NOMINAL

**SPIKE PROTECTION MODES:**  
LINE TO NEUTRAL, ZERO GROUND LEAKAGE

**SPIKE CLAMPING VOLTAGE:**  
375 VAC PEAK @3,000 AMPS

**RESPONSE TIME:**  
1 NANOSECOND

**MAXIMUM SURGE CURRENT:**  
6,500 AMPS

**NOISE ATTENUATION:**  
10 DB @ 10KHZ, 40 DB @ 100KHZ, 50 DB @500 KHZ

**DIMENSIONS:**  
482.6MM W X 266.7MM D X 44.45MM H

**WEIGHT:**  
6 KG

**POWER CONSUMPTION:**  
12 WATTS