



AX3 LightDrop™

Data sheet

Optical

- Colours
RGBW
- Total LED power
15W
- Luminous Flux
390Lm
- Emittance (@2m)
1300Lx
- Strobe
0-25Hz
- Beam Angle
13°
- Pixels
1

Electrical

- Battery
LG Chem Lithium-ion
- Battery Lifetime
70% after 300 cycles
- Battery Runtime
Up to 20 hours
- LED Lifetime
50.000 Hours
- Charging time (nominal)
7 Hours
- Input Voltage (charger)
90-264V 47-63Hz
- Input voltage (light)
5V 2.5A

Control

- Wireless Modules
865-870MHz
902-928MHz
2.4GHz
- Range
300m | 330 Yards
- DMX
Supports CRMX and W-DMX

Construction

- Housing
ABS
- IP Rating
IP65
- Relative humidity
0-100%
- Operating Temperature
0-40 °C
32-104 °F
- Weight
0.679kg
1.4Lbs
- Dimensions (with bracket)
120 x 59 x 114 (mm)
7.4 x 2.3 x 4.4 (inches)

Accessories

- Charger**
AX3-CHR (Included)
- Hooks (3)**
AX3-EBLT (Included)
- Rubber Feet (4)**
AX3-FEET (Included)
- Bracket**
AX3-STA (Included)
- 30° diffuser**
AX3-DDSK30 (Included)
- 120° diffuser**
AX3-DDSK-120(Included)
- Wallwash diffuser**
AX3-WWDSK
- Diffuser dome**
AX3-DDM
- Charging case**
AX3-CHRCSE
- Clamp**
AX3-CLP

3.8" screw thread
Compatible with Manfrotto
Bolt type 013

