



HELIOS TUBE

CHARGING CASE

Case to charge and carry 8 tubes and their main accessories
FP2-CHRCSE



Electrical

(Via FP1-PWB)
Input Voltage
90~250VAC

Current
4.4A @ 115VAC
3A @ 230VAC

Output Voltage
10 x 24 VDC

Output Current
10 x 2A

Power in
Via Powercon True1

Power out
Via Powercon True1

Construction

Material
ABS

Operating Temperature
0-40 °C
32-104 °F







Weight (empty)
15kg | 33.06lbs

Weight (full)
31kg | 61.34lbs

Dimensions
765 x 503 x 260mm
30.11 x 19.80 x 10inches

Environment
Indoor | Outdoor

Included in the set

-  PowerBox (x1)
FP1-PWB (+ 1x Powercon True1 cable
+ 8x DC connection cables)
-  Helios Tubes (x8)
FP2
-  Eyebolts (x16)
AX1-EBLT
-  Clamp (x16)
AX1-H
-  Stands (x8)
AX1-STD
-  BabyPin (x16)
AX1-BLT

Also can hold

-  WingPlates (x8)
AX1-WP

Note: The Helios Tube Charging Case is available in 2 versions:
- Set (order code: FP2-SET)
- Case (order code: FP2-CHRCSE)

Included in case

Included Connectors/Cables
1 x Powercon True1 cable
8 x DC connection cables

Drawings

