



HURACÁN WASH

JUST FOR A THRILL

OPTICS

- 13-element 12:1 zoom high-resolution optic system
- Beam aperture: 6.2° (half peak) to 75° (one-tenth peak)
- Fast motorised linear zoom
- Tempered anti-reflective coated lenses
- 210 mm Fresnel frontal lens

LIGHT SOURCE

HURACÁN WASH S

- 80,000-lumen white light engine
- Total luminaire output: up to 52,000 lumens (integrating sphere measurement, Auto Fan Mode)
- Colour temperature output: 7000 K
- CRI: greater than 70

HURACÁN WASH ST

- 68,000-lumen white light engine
- Total luminaire output: up to 45,000 lumens (integrating sphere measurement, Fan mode AUTO)
- Colour temperature output: 6000 K
- CRI: greater than 80

HURACÁN WASH TC

- 49,000-lumen white light engine
- Total luminaire output: up to 31,000 lumens (integrating sphere measurement, Auto Fan mode)
- Colour temperature output: 6000 K
- CRI: greater than 95

HURACÁN WASH (ALL VERSIONS)

- Rated life (L70): up to 40,000 hours
- Flicker-free source management suitable for TV applications and all video-recorded events

MOVEMENT

- Extremely accurate positioning
- Moving-head operated via either 8- or 16-bit resolution
- High-resolution stepper motors operated via microprocessors to ensure extreme accuracy and smooth movement
- Pan and tilt automatic repositioning
- Moving-head range: 540° (pan), 260° (tilt)

COLOURS

- Complex colour mixing system with a double CMY saturation level capable of generating trillions of colours (patent pending)

- Variable CTB colour temperature correction
- Variable CTO colour temperature correction
- Variable CTP colour temperature correction
- Fixed colour wheel with six complementary colours

GOBOS

- Indexable rotating gobo wheel with 7 high-precision glass gobos, plus open position
- Adjustable-speed rotating gobo in both directions
- Gobo diameter: 30.0 mm
- Image diameter: 25.0 mm
- Gobo thickness: 1.1 mm

FRAMING SYSTEM

- 4 individually positionable barndoors on a 100% surface area in all positions
- Rotation of the barndoors module: +/- 60°

IRIS DIAPHRAGM

- Fast iris diaphragm with adjustable dynamic effects
- Iris range: 15% to 100% open

FROST

- 0% to 100% variable linear frost

EFFECTS

- CMY & RGB colour graphic animation effects-wheel with continuous rotation in both directions
- Indexable de-focusable rotating beam-shaping optic

DIMMER / STROBE

- Electronic dimmer allowing perfect light adjustment from 0 to 100% without colour variation
- Strobe effect, with speed adjustment from 1 to 25 flashes per second

SOFTWARE FEATURES

- Local DMX addressing of luminaire and optional parameters through its built-in LCD control panel
- Remote DMX addressing of luminaire and optional parameters through a standard RDM DMX controller
- Information menu including hour counter, temperature, software version

HARDWARE FEATURES

- Graphic LCD display for addressing and special functions settings, with flip function
- Clicking jog wheel to set functions
- Excess-temperature protection
- Integrated wireless CRMX TIMO™ RDM receiver from LumenRadio™
- XLR 5-pin male and female connectors for DMX connection
- Ethercon RJ45 IN / OUT connectors for ArtNet™ connection
- PowerCON TRUE1 male and female connectors for power connection

CONTROL

- DMX 512 protocol, through DMX cable or a wireless system
- DMX RDM-compatible
- Stand-alone mode and Master/Slave modes
- ArtNet™ & sACN protocol through Ethernet cable
- Local control panel, with LCD display
- Choice of 3 DMX modes (from 39 to 61 DMX channels)

POWER SUPPLY

- Electronic supply with active PFC
- 120 to 240 Volts – 50/60Hz
- Power: 1,600 W maximum

COOLING SYSTEM

- Advanced liquid cooling system
- Self-adjusting variable speed fans for quiet operation (Auto mode)
- Selectable ventilation user modes including Super Silent Mode
- Safety protection against temperatures excesses

HOUSING

- Moving-head skeleton made of aluminium and steel plates
- Base in die-cast aluminium
- Heatsinks in aluminium and copper
- Moulded covers in self-extinguishing fire retardant ABS PC (V0 class)
- Two-side handles for transportation
- Four heavy-duty feet for better stability
- IP20 protection rating
- Exterior finish: black (Carbon)

INSTALLATION

- Fastening bracket system: two Omega ¼ turn brackets designed for use with standard clamps
- Mounting points: eight ¼ turn locking fittings allowing installation of Omega brackets on luminaire
- Safety-cable attachment point

OPERATING PARAMETERS

- Operating positions: all (device on floor or fixed to a support)
- Maximum permitted ambient temperature (Ta max): 45° C (113° F)
- Minimum permitted ambient temperature (Ta min): -10° C (14° F)
- Minimum usage distance: 3.0 m (9.84 ft.)

COMPLIANCE

EU (EMC & LVD)

- EMC Directive 2014/30/EU
- LVD Directive 2014/35/EU

US (Safety & EMC)

- UL 1573
- FCC Part 15, Subpart B: 2018

SIZE

- Product: 494 x 788 x 294 mm (l x h x d)
- Flight-case foam: 715 x 555 x 630 mm (l x h x d)

WEIGHT

- Product: 42.5 kg

PRODUCT CODES

- 011880: HURACÁN WASH S - CLASSICAL 9 SERIES
- 011883: HURACÁN WASH ST - CLASSICAL 9 SERIES
- 011885: HURACÁN WASH TC - CLASSICAL 9 SERIES

LEGAL

- HURACÁN is AYRTON registered Trademark
- HURACÁN is patent pending

OCTOBER 2022

Product shown are for illustration purposes only. Specifications subject to change without notice.



AYRTON
Digital Lighting